



12" LEFT AND RIGHT TILT TABLE SAW

The brawny JET® 12" Xacta®Saw is now available with a left-tilting arbor. Built with all of the same quality and high-performance JET® is known for, this serious machine gives users who prefer a left-tilting blade another choice when deciding which Xacta®Saw is right for them. This machine complete with a JET® Xacta®Fence, a powerful 5HP motor, huge cast iron trunnion, and industrial magnetic controls loves to flex its muscle with precision never being compromised.





12" LEFT AND RIGHT TILT TABLE SAW

- EXCLUSIVE 50" commercial XACTA® Fence II with T-square design
- Cast iron wings for a large, flat work surface
- Powerful 5HP, 3Ph motor makes even the toughest cutting jobs a breeze
- Three matched V-belts deliver full power to the blade
- Rail-mounted magnetic switch is easy to reach and provides overload protection
- One-piece closed stand channels dust through a 4" port for fast, clean dust collection
- Hinged motor cover on cabinet gives quick access to the motor and belts
- Large, heavy-duty handwheels help you make precise adjustments with less effort
- Built-in 4" port for dust collection
- See-through blade guard with splitter and anti-kickback pawls helps protect operator while giving a clear view of the material being cut

STOCK NUMBER	708536PK RIGHT TILT	708537PK LEFT TILT	708541PK RIGHT TILT	708542PK LEFT TILT
Model Number	JTAS-12X50-1	JTAS-12XL50-5/1	JTAS-12X50-3	JTAS-12XL50-3
Net Weight (lbs.)	593	518	580	518
Blade Diameter (in.)	12	12	12	12
Arbor Diameter (in.)	1	1	1	1
Arbor Speed (RPM)	4200	4200	4200	4200
Maximum Depth of Cut (in.)	4	4	4	4
Maximum Depth of Cut at 45 Degrees (in.)	2-7/8	2-7/8	2-7/8	2-7/8
Maximum Rip Right of Blade (in.)	50	50	50	50
Maximum Rip Left of Blade (in.)	13	13	13	13
Table in Front of Saw Blade at Maximum Depth of Cut (in.)	12	12	12	12
Maximum Width of Dado (in.)	13/16	13/16	13/16	13/16
Maximum Diameter of Dado (in.)	8	8	8	8
Table Height (in.)	34	34	34	34
Table Size with Standard Extension (L x W/in.)	29 x 44	29 x 44	29 x 44	29 x 44
Table Size without Extension (L x W/in.)	29 x 22	29 x 22	29 x 22	29 x 22
Dust Port Diameter (OD/in.)	4	4	4	4
Dust Collection Minimum CFM Required	350	350	350	350
Motor HP	5HP	5HP	5HP	5HP
Motor Phase	1Ph	1Ph	3Ph	3Ph
Motor Voltage	230V	230V	230/460V	230/460V
Prewired	—	—	460V* requires optional switch JTAS10-2238	460V* requires optional switch JTAS10-2238